

**IN THE CLAIMS**

Pursuant to 37 CFR §1.121(c), the claim listing, including the text of the claims, will serve to replace all prior versions of the claims, in the application.

Please amend claim 8 as follows:

Claims 1-5. (Canceled)

1           6. (Previously Presented) An electromechanical lock cylinder, comprising:  
2                   an outer shell having a bore formed therein and a cavity extending from the  
3 bore into the shell;  
4                   a barrel disposed within the bore in the shell and being rotatable relative  
5 thereto;  
6                   a side bar cooperating between the shell and the barrel for selectively  
7 permitting and blocking rotation of the barrel with respect to the shell, the side bar having  
8 a first portion engaging the barrel and a second portion removably received in the cavity in  
9 the shell, the side bar being movable relative to the barrel;  
10                  wherein at least one electromechanical locking member is disposed within the  
11 barrel and is positionable in a barrel blocking position blocking rotation of the barrel with  
12 respect to the shell, and also is positionable in a non-barrel blocking position permitting the  
13 side bar to be moved relative to the cavity in the shell to rotate the barrel with respect to the  
14 shell;  
15                  an electronically powered drive mechanism located within the barrel and  
16 cooperating with the electromechanical locking member to selectively move the locking  
17 member from the barrel blocking position to the non-barrel blocking position in which the  
18 side bar moves out of the cavity and engages the locking member; and  
19                  control means for activating the electronically powered drive mechanism in

20 response to an authorized attempt to operate the lock cylinder.

1           7. (Previously Presented) A lock cylinder according to claim 6, wherein the first  
2 portion of the side bar is an outer edge and the second portion is an opposite inner edge, and  
3 when the at least one locking member is in said barrel blocking position the outer edge of the  
4 side bar is received in the cavity formed in the shell, and wherein the at least one locking  
5 member has a groove which receives the inner edge of the side bar when the at least one  
6 locking member is in said non-barrel blocking position.

1           8. (Currently Amended) A rotatable lock barrel for insertion into a lock cylinder  
2 having a bore formed therein, the barrel comprising:

3           an elongated, generally cylindrically shaped barrel member having an exterior  
4 configured for receipt in a bore of a lock cylinder and an interior containing an  
5 electromechanical locking member, the barrel member having a recess formed therein;

6           wherein the locking member is disposed in the recess of the barrel member and is  
7 substantially entirely contained within the barrel member, the locking member including a  
8 groove and the locking member being movable to a position in which the groove of the  
9 locking member is placed in an alignment;

10           the recess in said barrel member permitting ~~[[the]]~~ a side bar to move into and out of  
11 engagement with the groove of the locking member for selectively permitting and blocking  
12 rotation of the barrel member with respect to a lock cylinder when positioned therein; and

13           an electronically powered drive mechanism located within the barrel member for  
14 moving the electromechanical locking member to a position in which the groove of the  
15 locking member is in said alignment.

1           9. (Previously Presented) A process of retrofitting a mechanical cylinder lock to  
2 form an electromechanical cylinder lock, the process comprising steps of:

3 providing a mechanical cylinder lock including an outer shell with a bore having a  
4 recess accommodating movement by a side bar, and a first rotatable barrel located in the  
5 bore;

6 removing the first barrel from the shell;

7 providing an electronically powered rotatable barrel including:

8 a side bar preventing and permitting rotation of the barrel within the  
9 bore in the shell;

10 an electromechanical locking member substantially entirely contained  
11 within the barrel member, the electromechanical locking member being  
12 positionable to permit the side bar to engage the locking member in a non-  
13 barrel blocking position which permits the barrel to rotate with respect to the  
14 shell, and the electromechanical locking member also being positionable to  
15 place the sidebar in a barrel blocking position which blocks rotation of the  
16 barrel with respect to the shell;

17 an electronically powered drive mechanism cooperating with the  
18 electromechanical locking member to selectively move the locking member  
19 from the barrel blocking position to the non-barrel blocking position in which  
20 the side bar engages the locking member to rotate the barrel and operate the  
21 lock; and

22 a controller carried by the barrel energizing the electronically powered  
23 drive mechanism in response to an authorized attempt to open the lock; and

24 inserting the electronically powered rotatable barrel into the bore in the shell to form  
25 an electromechanical cylinder lock.

1 10. (Previously Presented) A rotatable lock barrel for insertion into a lock cylinder  
2 having a bore formed therein, the barrel comprising:

3 an elongated, generally cylindrically shaped barrel member having an exterior

4 configured for receipt in a bore of a lock cylinder and an interior containing an  
5 electromechanical locking member, the barrel member having a recess formed therein;

6 wherein the locking member is disposed in the recess of the barrel member and is  
7 substantially entirely contained within the barrel member, the locking member including a  
8 groove;

9 the recess in said barrel member permitting the side bar to move into and out of  
10 engagement with the groove of the locking member for selectively permitting and blocking  
11 rotation of the barrel member with respect to a lock cylinder when positioned therein;

12 an electronically powered drive mechanism located within the barrel member moving  
13 the electromechanical locking member to a position in which the groove of the locking  
14 member is aligned to receive the side bar.

1 11. (Previously Presented) The process of claim 9, the process comprising steps of  
2 providing at least one additional electromechanical locking member disposed in the barrel,  
3 the additional electromechanical locking member being also positionable to permit the side  
4 bar to engage the locking member in a non-barrel blocking position which permits the barrel  
5 to rotate with respect to the shell.

1 12. (Previously Presented) The rotatable lock barrel of claim 10, comprising at least  
2 one additional electromechanical locking member substantially entirely contained within the  
3 barrel member, the additional locking member including a groove and being movable to a  
4 position in which the grooves of the locking members are aligned to permit the side bar to  
5 engage the locking member in a non-barrel blocking position which permits the barrel to  
6 rotate with respect to the shell.